





GMP RF F 10R THIN



Real Time Wireless Temperature Data Logger with Flexible Sensor -60°C to +85°C



- + Collects and transmits real time temperature to XpertLog Software
- + ITS-90 calibration coefficients are stored in the internal memory
- + Complies with FDA 21 CFR Part 11
- + Network ready: multiple users, centralized, server database, active directory authentication
- + Calibration can be performed on site
- + Can be remotely activated




Sensor type	4 wires thin
- flexible	150 mm (6") or custom length
- customized	up to 5000 mm (195")
- Sensor size	1.2 x 1.6 mm (0.05 x 0.06")
- cross section	0.48 mm ² (0.0007 inch ²)
Operating Range	
- body	-60°C to +85°C
- Sensor	-200°C to +140°C
Accuracy	±0.1°C from -60°C to +85°C
Resolution	0.01°C
Memory capacity	32,000 data points
Memory type	non volatile
Sampling rate	1 sec to 24 hours
Transmission	simultaneous: maximum 20 loggers
	sequential: unlimited
Internal clock drift	4 sec / 24 h @ 23°C
Mechanical	
- material	Peek 1000 - FDA compliant
- enclosure	IP-68
- weight	24 g (0.85 oz)
- diameter	25 mm (0.98")
- height	46 mm (1.81")
Power	1 x Lithium batteries, 0.35 g/each Lithium content classified UN3091 under IATA DGR section 3.9.2.6 compliant with ICAO/IATA packing instructions 970, user replaceable
Battery lifetime	Up to 2 months, based on usage
Antenna	Internal
Wireless range	121 m (400 feet)
Radio frequency	2.4 Ghz ISM band
Access point	USB to computer
Calibrations	Programs and reads unlimited number of loggers
	Factory Calibrations: traceable NIST/COFRAC - ITS-90 coefficients stored in the internal memory
	User Calibrations: closed loop calibration using XpertLog® software
Certification	Health Safety: EN 60950-1 / 2006
	EMC: EN 60601-1-2 / 2007
	RF: EN 300440-2 v1.3.1 (2009-03)

Order Reference

GMP-RF-F-10R-THIN
GMP-RF-F-10R-THIN-NOTIP

Standard Calibration Points

- -60°C
- 0°C
- 85°C



XpertLog
software

